


Project	
Item	
Quantity	
Approved	
Date	


# pratika ovens

# ELECTRIC COMBI OVEN TOUCH SCREEN, 10 TRAYS

Mod. FDE101TV







E - Electric cable stress relief

**D** - Water outlet

H2OA - Normal water inlet EN ISO 228-1 G 3/4

H20B - Softened water inlet EN ISO 228-1 G 3/4

#### **DESCRIPTION**

Electric multifunction oven with 5" capacitive touch screen. Double internal grid support, removable and replaceable, having gap between grids of 74 mm. 10-trays capacity GN 1/1 or EN 600x400. Three cooking modes: convection, steam and mixed. Equipped with recipe book and possibility to store personalized recipes (up to 16 cycles for each recipe). Cooking chamber in AISI 304 with rounded corners. Silicone gasket in the front of the cooking chamber easily removable. Gutter for the collection of liquid located under the door. Door with wide glass surface. Air channel for the external glass ventilation which limits the temperature on the external surface. 2 autoreverse fan with two-speed-fan regulation. Electronic air-valve opening. Heating through high efficiency coated heating elements. Adjustable heating on two power. Temperature control in the cooking chamber from 30° to 280° C. Led chamber lighting. Core probe and automatic washing system included.

## **ACCESSORIES INCLUDED**

Code	Qty	
561.115.00	1	Single point core probe
503.500.40	1	600x400 grid

	NET	GROSS
Dimensions - mm (LxDxH)	905x845x1106	955x900x1301
Weight - Kg	134,1	147,4
Volume - m3	-	1,12

### **TECHNICAL DATA**

Tot. ele power - kW	15,8	
Voltage - Volt	380-415 V 3 N	
Frequency - Hz	50-60	
Cable section - mmq	5 G 4	
Absorption - Ampere	26	
Capacity	10 GN 1/1 or 10 600x400	
Distance between grids - mm	74	

In the interest of continued improvements to our products, we reserve the right to change specifications, design and image at any time without prior notification, and without any obligation to update products already supplied.