



DESCRIPTION

Electric convection oven with manual control. Double internal grid support, removable and replaceable, having gap between grids of 74 mm. 5-trays capacity GN 1/1 or EN 600x400. Cooking chamber in AISI 304 with rounded corners. Silicone gasket in the front of the cooking chamber easily removable. Gutter for the collection of liquid located under the door. Door with wide glass surface. Air channel for the external glass ventilation which limits the temperature on the external surface. 1 autoreverse fan with two-speed-fan regulation. Manual air-valve opening. Heating through high efficiency coated heating elements. Temperature control in the cooking chamber from 30° to 280° C and timer from 1' to 120' (plus infinite position), manual humidifier. Led chamber lighting.

ACCESSORIES INCLUDED

Code	Qty
503.500.40	1 600x400 grid

	NET	GROSS
Dimensions - mm (LxDxH)	905x845x726	955x900x921
Weight - Kg	98	110,4
Volume - m3	-	0,791

TECHNICAL DATA

Tot. ele power - kW	7,9
Voltage - Volt	380-415 V 3 N
Frequency - Hz	50-60
Cable section - mmq	5 G 2,5
Absorption - Ampere	13,5
Capacity	5 GN 1/1 or 5 600x400
Distance between grids - mm	74